



Doosan Infracore
Construction Equipment



Portable Power

StonAir Series



Portable Air Compressor

StoneAir Series

Doosan "StonAir Series" portable air compressor is the "Best in Class" for 2 jack("StonAir 2"), 3 jack ("StonAir 3") hammer drilling. Compact, Quiet-running, Light Weight Design, Superior Running Gear and Fuel efficient Engine Ensures-Reliability, Safety and Efficiency.

"Value for Money" Compressors :

- Fuel economy.
- Lowest operating cost in its class.
- High air-end life.
- Enhanced engine life.
- High Reliability.

Performance Features :

- Better fuel economy.
- Patented air-end design – Superior volumetric efficiency, Enhanced life, Low engine rpm.
- Low engine rpm – Higher fuel efficiency and enhanced engine life.
- Specially blended lubricant – Extended warranty.
- Guaranteed pressure and flow at discharge valve.
- Best fit for 2 Jack hammer operation.
- Cool- Box – Keeps the internal canopy temperature low – Improves components life.
- Polymer fuel tank – Corrosion and rust free, light weight.
- Height adjustable tow bar for easy towing at site with different vehicles.
- Easy transportation – Compact and light weight.

Easy Serviceability :

- Lockable side doors for quick and easy access for service.
- Easy rear access encourages easy maintenance – for cleaning Radiator and Oil Cooler.
- Heavy duty single point lifting bail.

Engineered with Safety :

- Integrated automatic safety and shut down features for engine and compressor under the following conditions
 - » High discharge temperature.
 - » Low engine oil pressure.
 - » High engine water temperature.
- Auto blow down valve, safety valve, Air filter maintenance indicator.

Specifications :

Compressor models	Unit	StonAir 2	StonAir 3	
Performance				
Free Air Delivery*	CFM	260	340	
Rated Operating Pressure	PSI	100	100	
Engine				
Make	--	Ashok Leyland	Ashok Leyland	
Model	--	W04D	W04CT	
BHP	HP	78.4	101.3	
Rated Speed	rpm	2400	2300	
Dimensions				
Overall Length	mm	3535	3535	
Overall Width	mm	1740	1740	
Overall Height	mm	1850	1850	
Gross Weight	kg	1470	1505	
Max. Towing Speed	Km/hr	30	30	

*as per ISO 1217 Tolerance limit

*Product improvement is a continuing goal at Doosan. Design and specifications are subject to change without notice or obligation.



Doosan Infracore India Pvt. Ltd

3rd Floor, TNPL Building, No. 67, Mount Road, Guindy, Chennai - 600 032.

Tel : +91 44 4222 3900/915, Fax : +91 44 4222 3905, Toll Free : **1800 200 2299**

Email : marketingindia@doosan.com, www.doosaninfracore.com

Authorised Dealer