

TECHNICAL DATA

	Unit	AM 3 FH	AM 3 SH	AM 4 FH	AM 4 SH	AM 6 FHC2	AM 6 FHC2	AM 6 SHC2	AM 6 SHC2	AM 6 SHC2	AM 7 FHC2	AM 7 SHC2	AM 8 FHC2	AM 8 SHC2	AM 9 FHC2	AM 9 SHC2	AM 10 FHC2
Working Capacity	litre (m³)	3000 (3)	3000(3)	4000 (4)	4000 (4)	6000 (6)	6000 (6)	6000(6)	6000 (6)	6000(6)	7000 (7)	7000 (7)	8000(8)	8000(8)	9000 (9)	9000 (9)	10000 (10)
Gravel Volume	litre	6350	6350	7780	7780	11590	11590	11580	11580	11580	12750	12750	14170	14170	15850	15850	17080
Volume	litre	3450	3450	4600	4600	7186	7186	7186	7186	7250	7814	7814	8838	8838	10010	10010	10720
	%	47	47	51	51	52	52	52	52	52	55	55	56.5	56.5	56.8	56.8	58.5
Power	kw	28	39	38	39	52	52	49-52	49-52	49-52	52	49-52	63	79	79	79	79
	min ⁻¹	0-12	0-12	0-12	0-12	0-12	0-12	0-12	0-12	0-12	0-12	0-12	0-12	0-12	0-12	0-12	0-12
	litre	300*	300	300*	450	300 *	300 *	450	450	450	300 *	450	500 *	650	500 *	650	500 *
Oil of Gear Box	litre (App)	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	12	12	12	12	12
Oil of hydraulic system	litre (App)	19	19	19	19	19	19	19	19	19	19	19	19	19	19	19	19
Wheel	mm**	4500	4500	5000	5000	6150	6150	6000	6000	5900	6400	6250	6900	7250	7200	7700	7500
Wheel	mm	2300	2300	2350	2350	2400	2400	2400	2400	2400	2400	2400	2450	2450	2450	2450	2450
Wheel hopper to the chassis	mm ***	2546	2546	2377	2377	2588	2588	2663	2663	2610	2625	2653	2682	2682	2682	2722	2682
Wheel standard	Approx. Brnng	2.9	3.3	3.2	3.5	3.5	3.5	3.9	3.9	3.6	3.7	4.1	4.1	4.5	4.3	4.98	4.7
Weight concrete	to m³	7.2	7.2	9.6	9.6	14.4	14.4	14.4	14.4	14.4	16.8	16.8	19.2	19.2	21.6	21.6	24
Weight rating	to m³ ^d	10	10	16	16	25	25	25	25	25	25	25	31	31	31	31	31
Weight of mixer accessories: trailer with support Capacity: Fuel braided hoses, Weg. plates etc.)	kg	80	80	80	80	150	150	150	150	80	150	150	150	150	150	150	150

Standardised water system FH - Truck PTO driven

Weight with respect to chassis. SH - Separate engine drive

Weight tolerance ± 30 mm

Weight tolerance ± 5% accordance with DIN 70020

Weight with respect to Country regulations

Truck Mixers

Summary



SCHWING
Steffter

QUALITY FOR ALL REQUIREMENTS

SCHWING Stetter truck mixers are from the result of experience gained over decades accompanied by continuous advancement and optimization. They incorporate the know-how from a production of more than 80,000 truck mixers which have proved to be reliable all over the world. SCHWING Stetter truck mixers are characterized by low-maintenance technology in a modern design, simple handling, cost minimizing in maintenance and service, efficiency and excellent cost effectiveness.



MIXER WITH SLAVE ENGINE DRIVE



MIXER WITH PTO DRIVE



MIXER MOUNTED ON TRAILERS